



# 2

## ROLLING STOCK

IN THE RAILWAY SYSTEM

### EDITION 2020

---

Edited by  
Éric Fontanel and Reinhard Christeller  
with the support of François Lacôte



# Table of contents

|                                                                                             |    |
|---------------------------------------------------------------------------------------------|----|
| <b>Forewords</b>                                                                            | 14 |
| <b>Chapter 6: Rolling stock architecture</b>                                                | 19 |
| 6.0 Introduction to rolling stock design, functional and product breakdown structures       | 20 |
| 6.0.1 Essential functions and services assigned to rolling stock                            | 20 |
| 6.0.2 Main types of vehicles and train configurations                                       | 21 |
| Rail vehicles as single units                                                               | 22 |
| Fixed formation trains                                                                      | 22 |
| Trains of variable consist                                                                  | 23 |
| 6.0.3 Rolling stock design and validation                                                   | 23 |
| Rolling stock LCC stages                                                                    | 23 |
| Rolling stock design and validation processes                                               | 24 |
| Controlled adaptation process: platform and modularity concepts                             | 24 |
| Functional or product descriptive specifications ?                                          | 25 |
| 6.0.4 Role of stakeholders in rolling stock specification, design and validation phases     | 27 |
| Industrial design of rail vehicles                                                          | 28 |
| 6.0.5 RAMS Requirements                                                                     | 34 |
| 6.0.6 Validation, acceptance and authorisations to put on the market and in revenue service | 34 |
| 6.1 Urban rail                                                                              | 36 |
| 6.1.1 Trams, Light Rail Vehicles and Tram-Trains                                            | 38 |
| 6.1.1.1 General requirements                                                                | 38 |
| Infrastructure and operational conditions                                                   | 38 |
| 6.1.1.2 Integration into urban environment                                                  | 41 |
| 6.1.1.3 Legal and regulatory framework                                                      | 42 |
| 6.1.1.4 Tram architecture                                                                   | 43 |
| 6.1.1.4.1 Basic architectural principles                                                    | 48 |
| 6.1.1.4.2 Partial low-floor trams                                                           | 50 |
| 6.1.1.4.3 Full low-floor trams                                                              | 51 |
| 6.1.1.4.4 Transition to metro operation                                                     | 53 |
| 6.1.1.4.5 Tram-trains                                                                       | 54 |
| 6.1.1.4.6 Trams on tyres                                                                    | 56 |
| 6.1.2 Metros                                                                                | 58 |
| 6.1.2.1 Introduction and scope                                                              | 58 |
| 6.1.2.1.1 General                                                                           | 58 |
| 6.1.2.1.2 Definition                                                                        | 58 |
| 6.1.2.1.3 Categorisation and legal and regulatory framework                                 | 58 |
| 6.1.2.2 Essential performance features and services to passengers by the rolling stock      | 59 |
| 6.1.2.2.1 General                                                                           | 59 |
| 6.1.2.2.2 Passenger Capacity                                                                | 59 |
| 6.1.2.2.3 Means for quick passenger exchange                                                | 60 |
| 6.1.2.2.4 Acceleration and braking performance, top speed, headway                          | 60 |
| 6.1.2.2.5 Comfort                                                                           | 61 |
| 6.1.2.2.6 Safety                                                                            | 61 |
| 6.1.2.2.7 Summary                                                                           | 62 |
| 6.1.2.3 System characteristics essential to the metro rolling stock subsystem               | 62 |
| 6.1.2.3.1 General                                                                           | 62 |
| 6.1.2.3.2 Gauging, track work, tunnels, stations                                            | 64 |
| 6.1.2.3.2.1 Gauging                                                                         | 64 |
| 6.1.2.3.2.2 Track work for steel wheel systems                                              | 65 |
| 6.1.2.3.2.3 Tunnels                                                                         | 66 |
| 6.1.2.3.2.4 Stations                                                                        | 67 |
| 6.1.2.3.3 Power supply                                                                      | 67 |
| 6.1.2.3.4 Signalling system, and automatic train control                                    | 68 |
| 6.1.2.3.5 Tunnel operation and operation on elevated structures                             | 69 |
| 6.1.2.4 Typical examples for every system – Metro architecture                              | 70 |
| 6.1.2.4.1 Train configuration                                                               | 70 |
| 6.1.2.4.2 Cross section and layout                                                          | 71 |
| 6.1.2.4.3 Subsystems                                                                        | 72 |

## Rolling Stock in the Railway System

|                                                                                           |     |
|-------------------------------------------------------------------------------------------|-----|
| 6.1.2.4.3.1 Bodies and comfort                                                            | 72  |
| 6.1.2.4.3.2 Bogies and dynamics                                                           | 74  |
| 6.1.2.4.3.3 Braking and air production                                                    | 74  |
| 6.1.2.4.3.4 Train control                                                                 | 76  |
| 6.1.2.4.3.5 Traction                                                                      | 77  |
| 6.1.2.5 Limitation to performance                                                         | 78  |
| 6.1.2.6 Different sub-categories in Europe in terms of operations and infrastructures     | 79  |
| 6.1.2.7 Standardisation and vehicle platforms – why and how.                              | 79  |
| 6.1.2.7.1 Reasons                                                                         | 79  |
| 6.1.2.7.2 Examples for metro platforms                                                    | 79  |
| 6.1.2.7.2.1 Metropolis (Alstom)                                                           | 79  |
| 6.1.2.7.2.2 MOVIA (Bombardier Transportation)                                             | 80  |
| 6.1.2.7.2.3 INNOVIA Metro 300 (Bombardier Transportation)                                 | 80  |
| 6.1.2.7.2.4 AT100 (Hitachi)                                                               | 80  |
| 6.1.2.7.2.5 Inspiro (Siemens)                                                             | 81  |
| 6.1.2.7.2.6 Inneo (CAF)                                                                   | 81  |
| 6.1.2.7.2.7 Driverless metros (Hitachi Rail Italy, formerly AnsaldoBreda)                 | 81  |
| 6.1.2.7.2.8 Others                                                                        | 81  |
| 6.1.2.8 Rubber-tyred metros                                                               | 82  |
| 6.1.2.8.1 Introduction                                                                    | 82  |
| 6.1.2.8.2 History                                                                         | 82  |
| 6.1.2.8.3 A variety of rolling stock configurations                                       | 83  |
| 6.1.2.8.4 People Movers                                                                   | 84  |
| 6.1.2.8.4.1 General                                                                       | 84  |
| 6.1.2.8.4.2 The VAL concept                                                               | 84  |
| 6.1.2.8.4.3 The Neoval Concept                                                            | 86  |
| 6.1.2.8.4.4 Other People Movers                                                           | 86  |
| 6.1.2.8.5 Rubber-tyred medium-sized metros                                                | 87  |
| 6.1.2.8.5.1 Bombardier metros                                                             | 87  |
| 6.1.2.8.5.2 CAF metros                                                                    | 88  |
| 6.1.2.8.5.3 Alstom metros                                                                 | 88  |
| 6.1.2.8.5.4 Other suppliers                                                               | 90  |
| 6.1.2.9 Technology evolution                                                              | 90  |
| 6.1.2.10 Using IT for operation and passengers – always connected                         | 91  |
| 6.1.2.11 Automatic train operation (ATO) in metros                                        | 91  |
| 6.1.2.11.1 General                                                                        | 91  |
| 6.1.2.11.2 Configuration                                                                  | 91  |
| 6.1.2.11.3 Specific requirements for metro trains                                         | 91  |
| 6.2 Commuter, regional and intercity trains                                               | 94  |
| Definition                                                                                | 94  |
| Economic comparison of locomotive hauled and self-propelled trains                        | 95  |
| Parameters with an impact on the cost per kilometre of an operation                       | 95  |
| Parameters with an influence on the choice between locomotive-hauled trains and trainsets | 95  |
| Analysis                                                                                  | 95  |
| Daily variations                                                                          | 95  |
| Seasonal variations                                                                       | 96  |
| Offered services and train staff                                                          | 96  |
| Complexity of the traction system                                                         | 97  |
| Axle load                                                                                 | 97  |
| Type of service                                                                           | 97  |
| Comparison of investments                                                                 | 98  |
| 6.2.1 Loco-hauled trains                                                                  | 99  |
| 6.2.1.1 Short history of coaches and loco-hauled trains                                   | 99  |
| 6.2.1.2 Regulatory framework                                                              | 100 |
| 6.2.1.3 Reasons to replace loco-hauled trains                                             | 102 |
| 6.2.1.4 Operational aspects of loco-hauled trains and impact on station layout            | 102 |
| 6.2.1.5 Generic coach design                                                              | 102 |
| 6.2.1.6 UIC coaches                                                                       | 103 |
| 6.2.1.7 Unconventional locomotive-hauled trains for long-distance traffic                 | 105 |
| 6.2.1.8 Coaches for long-distance traffic in North America                                | 106 |
| 6.2.1.9 Coaches for commuter services in North America                                    | 106 |
| 6.2.1.10 Other coaches and locomotive-hauled train units                                  | 107 |

|            |                                                                                   |     |
|------------|-----------------------------------------------------------------------------------|-----|
| 6.2.1.11   | Technical description of modern coaches                                           | 108 |
| 6.2.1.11.1 | Siemens Viaggio – ÖBB-Railjet                                                     | 108 |
| 6.2.1.11.2 | Russian sleeping cars from Transmashholding                                       | 109 |
| 6.2.1.11.3 | The Tibet train                                                                   | 110 |
| 6.2.1.11.4 | Standard-coaches for developing countries                                         | 111 |
| 6.2.1.12   | Coach components                                                                  | 111 |
| 6.2.1.12.1 | Power supply for coaches                                                          | 111 |
| 6.2.1.12.2 | Couplers, buffers and gangways between coaches                                    | 112 |
| 6.2.1.12.3 | Pneumatic equipment                                                               | 112 |
| 6.2.1.12.4 | Doors and accessibility                                                           | 112 |
| 6.2.1.12.5 | Communication and control systems in locomotive-hauled coaches                    | 113 |
| 6.2.1.12.6 | Push-pull issues                                                                  | 114 |
| 6.2.2      | Trainsets                                                                         | 115 |
| 6.2.2.1    | Short History                                                                     | 115 |
| 6.2.2.2    | Regulatory framework                                                              | 116 |
| 6.2.2.3    | Design                                                                            | 116 |
| 6.2.2.3.1  | Design characteristics                                                            | 116 |
| 6.2.2.3.2  | Design drivers                                                                    | 119 |
| 6.3        | High-speed and very high-speed trains                                             | 128 |
| 6.3.1      | Alternatives to the wheel-rail system                                             | 128 |
| 6.3.1.1    | The Hovertrain (“aérotrain”)                                                      | 128 |
| 6.3.1.2    | Germany: the Transrapid                                                           | 129 |
| 6.3.1.3    | Japan: the Maglev Project                                                         | 129 |
| 6.3.1.4    | Concepts underpinned by a false premise from the outset                           | 129 |
| 6.3.1.5    | Drawbacks as opposed to the wheel-rail system                                     | 130 |
| 6.3.2      | Issues relevant to high-speed rail                                                | 131 |
| 6.3.2.1    | High-speed tilting trains                                                         | 131 |
| 6.3.2.2    | Very high speeds on dedicated new line                                            | 132 |
| 6.3.3      | Train design constraints imposed by high speeds                                   | 132 |
| 6.3.3.1    | Physical phenomena evolving continuously with speed                               | 133 |
| 6.3.3.1.1  | Wheel-rail adhesion                                                               | 133 |
| 6.3.3.1.2  | The train resistance to motion (with stationary aerodynamics drag)                | 134 |
| 6.3.3.1.3  | Aerodynamic phenomena specific to high speeds                                     | 136 |
| 6.3.3.2    | Threshold phenomena                                                               | 139 |
| 6.3.3.2.1  | Current collection and catenary critical speed                                    | 139 |
| 6.3.3.2.2  | Bogie dynamic stability and critical speed                                        | 139 |
| 6.3.4      | Architectures of high-speed trains                                                | 144 |
| 6.3.4.1    | Multi-drive systems                                                               | 144 |
| 6.3.4.2    | Fixed-composition “block” trainsets                                               | 144 |
| 6.3.4.3    | The issue of distributed versus concentrated drive                                | 145 |
| 6.3.5      | Recent developments                                                               | 146 |
| 6.3.5.1    | Asia                                                                              | 146 |
| 6.3.5.2    | Middle East and North Africa                                                      | 147 |
| 6.3.5.3    | Europe                                                                            | 148 |
| 6.3.6      | What next for high-speed rail?                                                    | 150 |
| 6.4        | Freight wagons                                                                    | 152 |
| 6.4.1      | Freight wagon types                                                               | 152 |
| 6.4.1.1    | E-type: open wagons (standard)                                                    | 153 |
| 6.4.1.2    | F-type: open wagons (specialised)                                                 | 153 |
| 6.4.1.3    | G-type: covered wagons (standard)                                                 | 154 |
| 6.4.1.4    | H-type: covered wagons (specialised)                                              | 154 |
| 6.4.1.5    | I-type: temperature-controlled wagons                                             | 154 |
| 6.4.1.6    | K-type: flat wagons with 2 wheelsets                                              | 154 |
| 6.4.1.7    | L-type: flat wagons with independent wheelsets (e.g. short coupled 2-axle wagons) | 155 |
| 6.4.1.8    | O-type: open flat wagons                                                          | 155 |
| 6.4.1.9    | R-type: flat wagons with 4 wheelsets                                              | 155 |
| 6.4.1.10   | S-type: flat wagon equipped with bogies                                           | 155 |
| 6.4.1.11   | T-type: wagons with an opening roof                                               | 156 |
| 6.4.1.12   | U-type: dedicated wagons (e. g. pressure differential tanks for cement)           | 156 |
| 6.4.1.13   | Z-type: tank cars                                                                 | 156 |
| 6.4.1.14   | Intermodal wagons                                                                 | 157 |
| 6.4.1.15   | Overview                                                                          | 157 |

|                                                   |     |
|---------------------------------------------------|-----|
| 6.4.2 European wagon components                   | 158 |
| 6.4.2.1 Brakes                                    | 158 |
| 6.4.2.2 Wheelsets and bogies                      | 158 |
| 6.4.2.3 Buffers                                   | 158 |
| 6.4.2.4 Couplers                                  | 159 |
| 6.4.3 Freight trains in the transportation system | 159 |
| 6.4.3.1 Freight train operations                  | 159 |
| 6.4.3.2 Constraints                               | 159 |
| 6.4.4 Innovative freight wagon systems            | 160 |
| 6.4.4.1 Mega Swing                                | 160 |
| 6.4.4.2 ModaLohr                                  | 160 |
| 6.4.4.3 CargoBeamer                               | 160 |
| 6.4.4.4 RailRunner                                | 161 |
| 6.4.4.5 Container-mover 3020                      | 161 |
| 6.4.5 Rolling motorway                            | 162 |

## Chapter 7: Mechanical subsystems 165

|                                                                                   |     |
|-----------------------------------------------------------------------------------|-----|
| 7.1 Passenger comfort and associated train arrangements                           | 166 |
| 7.1.1 Definition and components of rail comfort                                   | 166 |
| 7.1.1.1 Definition of rail comfort                                                | 166 |
| 7.1.1.2 Functional analysis: groups and functions according to EN 15380-4         | 168 |
| 7.1.1.3 Railway comfort measurement                                               | 170 |
| 7.1.1.4 The different components of rail comfort                                  | 171 |
| 7.1.1.4.1 Physical factors related to the environment                             | 171 |
| 7.1.1.4.2 Social factors related to the situation of transport                    | 171 |
| 7.1.1.4.3 Individual factors                                                      | 171 |
| 7.1.1.4.4 Temporal aspects of comfort                                             | 172 |
| 7.1.1.5 Overall comfort                                                           | 172 |
| 7.1.1.5.1 Synergy effect                                                          | 172 |
| 7.1.1.5.2 Mask effect                                                             | 172 |
| 7.1.1.6 Analysis of the different components of comfort                           | 173 |
| 7.1.1.7 Psychophysics                                                             | 173 |
| 7.1.2 Comfort components related to the environment                               | 175 |
| 7.1.2.1 Space factors                                                             | 175 |
| 7.1.2.1.1 Habitability                                                            | 175 |
| 7.1.2.1.2 Postural comfort                                                        | 178 |
| 7.1.2.1.3 How to measure the different components of static postural comfort      | 188 |
| 7.1.2.1.4 Efforts to be withstood by the seat                                     | 189 |
| 7.1.2.1.5 Dynamic comfort                                                         | 189 |
| 7.1.2.2 Accessibility factors and passenger flows                                 | 189 |
| 7.1.2.2.1 Accessibility                                                           | 192 |
| 7.1.2.2.2 Passenger flows                                                         | 193 |
| 7.1.2.2.3 Steps and doors                                                         | 194 |
| 7.1.2.3 Dynamic factors                                                           | 201 |
| 7.1.2.3.1 Acoustic comfort                                                        | 201 |
| 7.1.2.3.2 Psychoacoustic indicators                                               | 209 |
| 7.1.2.3.3 How to reduce acoustic disturbance                                      | 215 |
| 7.1.2.3.4 Vibration comfort                                                       | 216 |
| 7.1.2.3.5 Tympanic comfort                                                        | 227 |
| 7.1.2.4 Surroundings factors                                                      | 228 |
| 7.1.2.4.1 Thermal comfort and air quality                                         | 228 |
| 7.1.2.4.2 Design of heating and air conditioning for satisfactory thermal comfort | 237 |
| 7.1.2.4.3 Visual comfort                                                          | 244 |
| 7.1.2.5 Services and comfort on board                                             | 249 |
| 7.1.2.5.1 Arrangements on board trains - impacts on diagrams                      | 249 |
| 7.1.2.5.2 Specific areas dedicated to families, or dedicated to business trips    | 250 |
| 7.1.2.5.3 Ambiances on board                                                      | 250 |
| 7.1.2.5.4 Restaurant services                                                     | 251 |
| 7.1.2.5.5 Toilets                                                                 | 251 |
| 7.1.2.5.6 Luggage                                                                 | 253 |
| 7.1.2.5.7 Information on board                                                    | 254 |



|                                                                                  |     |
|----------------------------------------------------------------------------------|-----|
| 7.1.3 Individual comfort components                                              | 255 |
| 7.1.3.1 Age and gender                                                           | 255 |
| 7.1.3.2 Anthropometry                                                            | 255 |
| 7.1.3.3 Bubble of intimacy                                                       | 256 |
| 7.1.4 The temporal aspects of comfort                                            | 257 |
| 7.1.5 Overall comfort                                                            | 257 |
| 7.1.5.1 Simplified approach                                                      | 257 |
| 7.1.5.1.1 Sensory component indicator                                            | 257 |
| 7.1.5.1.2 Overall indicator                                                      | 258 |
| 7.1.5.2 Multi-criteria approach                                                  | 259 |
| 7.1.5.2.1 Presentation of the model                                              | 259 |
| 7.1.5.2.2 Application to thermal comfort                                         | 260 |
| 7.1.6 Interior fittings                                                          | 261 |
| 7.1.6.1 Face lining                                                              | 261 |
| 7.1.6.2 Windows                                                                  | 262 |
| 7.1.6.3 Seats and tablets                                                        | 263 |
| 7.1.6.3.1 Materials                                                              | 263 |
| 7.1.6.3.2 Fasteners                                                              | 263 |
| 7.1.6.4 Floors                                                                   | 263 |
| 7.1.6.5 Ceilings                                                                 | 264 |
| 7.1.6.6 Toilets                                                                  | 265 |
| 7.1.6.7 Interior doors                                                           | 265 |
| 7.1.6.8 Gangways between cars                                                    | 265 |
| 7.1.6.8.1 Intercommunication tunnels                                             | 265 |
| 7.1.6.8.2 Gangway doors                                                          | 266 |
| 7.1.6.9 Fire safety standards for railway rolling stock                          | 266 |
| 7.1.6.9.1 Evolution of European standards and regulations                        | 266 |
| 7.1.6.9.2 EN 45545 scope and objectives                                          | 267 |
| 7.1.6.9.3 EN 454545-1                                                            | 268 |
| 7.1.6.9.4 EN 45545-2                                                             | 269 |
| 7.1.6.9.5 EN 45545-3                                                             | 272 |
| 7.1.6.9.6 EN 45545-4                                                             | 273 |
| 7.1.6.9.7 EN 45545-5                                                             | 273 |
| 7.1.6.9.8 EN 45545-6                                                             | 274 |
| 7.1.6.9.9 EN 45545-7                                                             | 274 |
| 7.1.6.9.10 EN 50553: running capability                                          | 274 |
| Noise and vibrations: Impact upon local residents                                | 274 |
| Appendix 7 – I Design of passenger areas reducing the risk in case of collision  | 277 |
| I.1 Introduction                                                                 | 277 |
| I.2 The emergence of a need for interiors passive safety provisions in the UK    | 277 |
| I.3 The part played by the SafeInteriors project                                 | 278 |
| I.3.1 Objectives                                                                 | 278 |
| I.3.2 Levels of Injury severity                                                  | 278 |
| I.3.3 Injury criteria associated with body parts                                 | 279 |
| I.4 Description of a feasible standard and the rationale behind the requirements | 279 |
| I.5 Design of a passenger compartment compliant with passive safety requirements | 280 |
| I.5.1 Design methodology                                                         | 280 |
| I.5.2 Occupants containment                                                      | 280 |
| I.5.3 Injuries to passengers                                                     | 281 |
| I.5.4 Minimising passenger injury                                                | 282 |
| I.5.5 Effect of seat locations and other features                                | 282 |
| I.6 Assessment methods of occupied areas                                         | 283 |
| I.7: Elaboration of standards and regulatory aspects in Europe                   | 284 |
| Appendix 7 – II Detailed calculation of various terms related to thermal comfort | 285 |
| II.1 Metabolic rate                                                              |     |
| II.2 Thermal exchange with the environment                                       | 286 |
| II.2.1 Respiration exchanges                                                     | 286 |
| II.2.2 Exchanges by conduction                                                   | 286 |
| II.2.3 Exchanges by convection                                                   | 286 |
| II.2.4 Exchanges by radiation                                                    | 287 |
| II.2.5 Influence of clothing                                                     | 287 |

|             |                                                                              |     |
|-------------|------------------------------------------------------------------------------|-----|
| 7.2         | Vehicle body structures                                                      | 290 |
| 7.2.1       | Foreword                                                                     | 290 |
| 7.2.2       | Short history                                                                | 290 |
| 7.2.3       | Functions of a body structure                                                | 292 |
| 7.2.4       | Constraints impacting on body structure design                               | 294 |
| 7.2.4.1     | Mass and mechanical strength considerations                                  | 295 |
| 7.2.4.2     | Design interfaces and building constraints                                   | 296 |
| 7.2.5       | Description of a body structure                                              | 297 |
| 7.2.6       | Dimensioning of the body structure                                           | 298 |
| 7.2.6.1     | Load cases                                                                   | 298 |
| 7.2.6.1.1   | Reminder of the loads                                                        | 298 |
| 7.2.6.1.2   | Definition of the masses to be taken into account                            | 299 |
| 7.2.6.2     | Criteria for assessing conformity with proof and service loads               | 299 |
| 7.2.6.3     | Technical requirements relating to construction                              | 300 |
|             | The endurance limit method                                                   | 301 |
|             | The cumulative damage method                                                 | 302 |
| 7.2.6.4     | Definition of contractual loads                                              | 302 |
| 7.2.6.4.1   | Proof loads                                                                  | 302 |
| 7.2.6.4.2   | Service loads                                                                | 303 |
| 7.2.6.5     | Strength of fastenings for equipment attached to the vehicle body            | 303 |
| 7.2.6.5.1   | Proof loads for determining the required resistance of equipment fixings     | 303 |
| 7.2.6.5.2   | Fatigue loads for defining equipment fixings on the body                     | 303 |
| 7.2.6.6     | Design and validation by calculation                                         | 304 |
| 7.2.6.6.1   | Equations modelled in FEA structure calculations                             | 305 |
| 7.2.6.6.2   | Validation by calculation using FEA                                          | 305 |
| 7.2.6.7     | Test-based validation                                                        | 306 |
| 7.2.7       | Materials                                                                    | 306 |
| 7.2.7.1     | Steels                                                                       | 307 |
| 7.2.7.1.1   | Steel is universal                                                           | 307 |
| 7.2.7.1.2   | Example of a steel structure                                                 | 308 |
| 7.2.7.2     | Aluminium alloys                                                             | 308 |
| 7.2.7.2.1   | Aluminium is also universal                                                  | 308 |
| 7.2.7.2.2   | Examples of aluminium structures                                             | 308 |
| 7.2.7.3     | Composite materials                                                          | 309 |
| 7.2.7.4     | Selection criteria and specific structural issues                            | 310 |
| 7.2.7.4.1   | Railway applications based on steel                                          | 311 |
| 7.2.7.4.1.1 | Vehicle underframe                                                           | 312 |
| 7.2.7.4.1.2 | Body side walls                                                              | 313 |
| 7.2.7.4.1.3 | Roofs                                                                        | 314 |
| 7.2.7.4.2   | Railway applications using aluminium                                         | 315 |
| 7.2.7.4.2.1 | Body sidewalls                                                               | 315 |
| 7.2.7.4.2.2 | The roof                                                                     | 316 |
| 7.2.7.4.3   | Railway applications using stainless steel                                   | 316 |
| 7.2.7.4.4   | Body end designs                                                             | 317 |
| 7.2.7.4.4.1 | With a driving cab                                                           | 317 |
| 7.2.7.4.4.2 | With gangway                                                                 | 317 |
| 7.2.8       | Assembly procedures                                                          | 317 |
| 7.2.9       | Construction of a railway vehicle body                                       | 317 |
| 7.2.9.1     | Underframe assembly                                                          | 318 |
| 7.2.9.2     | Bodyside assembly                                                            | 319 |
| 7.2.9.3     | Assembling the vehicle roof                                                  | 320 |
| 7.2.9.4     | Fitting of body components in the assembly jig                               | 320 |
| 7.2.9.5     | Smoothing the sides of the assembled body                                    | 320 |
| 7.2.9.6     | Painting                                                                     | 321 |
| 7.2.9.7     | Film based protection                                                        | 323 |
| 7.2.9.8     | Interfaces and sequential construction                                       | 323 |
| 7.2.10      | Body construction using pre-equipped body modules assembled by cold jointing | 323 |
| 7.2.10.1    | Objectives                                                                   | 323 |
| 7.2.10.2    | Application to Citadis trams                                                 | 324 |
| 7.2.10.2.1  | Configurations                                                               | 325 |
| 7.2.10.2.2  | The components                                                               | 325 |
| 7.2.10.2.3  | Benefits and disadvantages                                                   | 325 |



|                                                                                        |     |
|----------------------------------------------------------------------------------------|-----|
| 7.2.11 Results of calculations and validation by testing                               | 327 |
| 7.2.11.1 Calculation results                                                           | 327 |
| 7.2.11.1.1 An example of FEA modelling                                                 | 327 |
| 7.2.11.1.2 Example of static calculations                                              | 327 |
| 7.2.11.1.3 Example of a dynamic calculation                                            | 328 |
| 7.2.11.1.4 Example of a fatigue analysis                                               | 328 |
| 7.2.11.2 Tests                                                                         | 329 |
| 7.2.12 Carbody maintenance                                                             | 330 |
| 7.2.12.1 Definition                                                                    | 330 |
| 7.2.12.2 Damage linked to service life (fatigue)                                       | 330 |
| 7.2.12.3 Damage linked to corrosion                                                    | 331 |
| 7.2.12.4 Accident damage                                                               | 331 |
| 7.2.12.5 Modifications and evolutions of an existing vehicle structure                 | 332 |
| 7.2.13 Crashworthiness                                                                 | 333 |
| 7.2.13.1 Example of TGV Duplex, an innovative development preceding EU standardisation | 333 |
| 7.2.13.1.1 Early crash evidence                                                        | 333 |
| 7.2.13.1.2 Design implications for vehicle body structures                             | 334 |
| 7.2.13.1.3 Strategic design options                                                    | 335 |
| Impact dynamics for a moving vehicle (reminder)                                        | 335 |
| 7.2.13.1.4 Design of the sacrificial zone                                              | 337 |
| 7.2.13.1.5 Manufacturing and testing: from the energy absorber to the trailer          | 337 |
| The vehicle frame                                                                      | 338 |
| Complete trailer                                                                       | 338 |
| Trailer Crash Test:                                                                    | 339 |
| 7.2.13.1.6 Power car crashworthiness                                                   | 339 |
| Analysis and specification                                                             | 339 |
| Design of the energy absorption areas                                                  | 340 |
| Power car crash tests                                                                  | 341 |
| 7.2.13.1.7 Test analysis and difficulties to overcome                                  | 343 |
| 7.2.13.1.8 Generalisation of the approach through standards                            | 343 |
| 7.2.13.2 Standardisation and European regulations                                      | 344 |
| 7.2.13.2.1 General principles governing EN 15227                                       | 344 |
| 7.2.13.2.2 Rolling stock categories                                                    | 345 |
| 7.2.13.2.3 Regulatory status of the standard                                           | 345 |
| 7.2.13.2.4 Crash scenarios in the EN 15227 standard                                    | 346 |
| Collision scenarios for category C-I vehicles                                          | 346 |
| Collision scenarios for vehicles of category C-II                                      | 349 |
| Collision scenarios for category C-III vehicles                                        | 349 |
| Collision scenarios for category C-IV vehicles                                         | 349 |
| 7.2.13.2.5 General and specific requirements                                           | 350 |
| 7.2.13.2.6 Practices in the other regions of the world                                 | 351 |
| United States (Federal Railroad Administration safety laws and regulations)            | 351 |
| Rest of the world                                                                      | 351 |
| 7.2.13.2.7 Testing and validation                                                      | 351 |
| Step 1 – Pre-test                                                                      | 352 |
| Step 2 – Testing                                                                       | 352 |
| Step 3 Post-test analysis                                                              | 353 |
| 7.2.13.2.8 Design cases                                                                | 353 |
| The Bombardier AGC regional train and Talent platforms                                 | 353 |
| Articulated trainsets                                                                  | 354 |
| Alstom AGV                                                                             | 354 |

## Rolling Stock in the Railway System

|                                                            |     |
|------------------------------------------------------------|-----|
| Appendix 7 - III: Structural Materials                     | 356 |
| III.1. Steels                                              | 356 |
| III.1.1 Steel manufacture                                  | 356 |
| III.1.2 Steel grades                                       | 358 |
| Composition and heat treatment of steels                   | 358 |
| III.1.3 Steel grade standardisation                        | 360 |
| III.1.4 Steel for machine welded bogie frames              | 362 |
| III.2. Aluminium                                           | 363 |
| III.2.1 Aluminium manufacture                              | 363 |
| III.2.2 Aluminium grades                                   | 365 |
| III.2.3 Composition and heat treatment of aluminium        | 366 |
| III.2.4 Advantages and drawbacks of aluminium              | 367 |
| III.3 Composites                                           | 367 |
| III.3.1 The materials                                      | 367 |
| III.3.1.1 Reinforcements                                   | 367 |
| III.3.1.2 The matrix                                       | 368 |
| III.3.1.3 The fillers                                      | 368 |
| III.3.1.4 Semi-finished products                           | 368 |
| III.3.2 Application technologies                           | 369 |
| III.3.2.1 Contact moulding                                 | 369 |
| III.3.2.2 Vacuum moulding                                  | 369 |
| III.3.2.3 Moulding by filament winding                     | 370 |
| III. 3.3 The various products                              | 370 |
| III.3.4 Calculations                                       | 370 |
| III.3.5 Testing                                            | 371 |
| III.3.6 Repair of composites                               | 371 |
| III.4 Selection criteria                                   | 373 |
| Appendix 7 - IV: Mechanical assembly methods               | 374 |
| IV.1 Permanent assembly: welding                           | 374 |
| IV.1.1 TIG welding                                         | 375 |
| IV.1.2 MIG-MAG (Metal inert gas- metal active gas) welding | 376 |
| IV.1.3 Resistance welding                                  | 376 |
| IV.1.4 Laser welding                                       | 377 |
| IV.1.5 Laser / MIG hybrid welding                          | 378 |
| IV.1.6 Operations subsequent to welding                    | 378 |
| IV.1.7 Friction Stir Welding (FSW)                         | 379 |
| IV.1.8 Explosion welding                                   | 380 |
| IV.1.9 Problems related to welding                         | 381 |
| IV.1.9.1 Metallurgical problems                            | 381 |
| IV.1.9.2 Mechanical problems                               | 381 |
| IV.1.9.3 Problems related to welding: weld defects         | 382 |
| IV.2 Permanent assembly by bonding                         | 382 |
| IV.3 Permanent assemblies - rivets and blind rivets        | 384 |
| IV.3.1 Riveting                                            | 384 |
| IV.3.2 Structural blind rivets                             | 385 |
| IV.4 Separable assemblies                                  | 386 |
| IV.4.1 Bolting: the bolt / nut system                      | 386 |
| IV.4.2 Bolts with calibrated preload                       | 387 |
| Appendix 7 - V: Finite element analysis                    | 389 |
| V.1 Introduction                                           | 389 |
| V.2 Physical problem: Linear elasticity example            | 391 |
| V.2.1 Stresses                                             | 391 |
| V.2.2 Deformations                                         | 392 |
| V.3 Mathematical model: Integral formulation               | 395 |
| V.4 Putting the variational integral into discrete form    | 396 |
| V.5 Accuracy                                               | 398 |
| V.6 Remarks                                                | 399 |
| 7.3 Running gear                                           | 400 |
| 7.3.1 Running gear elements                                | 400 |
| 7.3.1.1 Main purposes and high-level functions             | 400 |
| 7.3.1.2 The running gear as a part of the railway system   | 401 |
| 7.3.1.3 Interface to the infrastructure                    | 401 |

|              |                                                            |     |
|--------------|------------------------------------------------------------|-----|
| 7.3.1.3.1    | Wheel/rail interaction                                     | 401 |
| 7.3.1.3.2    | Wheel/rail forces                                          | 402 |
| 7.3.1.3.3    | Running stability                                          | 403 |
| 7.3.1.3.4    | Safety against derailment                                  | 403 |
| 7.3.1.3.5    | Wayside monitoring devices                                 | 404 |
| 7.3.1.4      | Interface to other rolling stock subsystems                | 406 |
| 7.3.1.5      | Relevant regulations                                       | 406 |
| 7.3.1.6      | Description of the running gear                            | 407 |
| 7.3.1.6.1    | A little history                                           | 407 |
| 7.3.1.6.2    | Main functions                                             | 408 |
| 7.3.1.6.3    | Main requirements and challenges                           | 410 |
| 7.3.1.6.4    | Main concepts                                              | 410 |
| 7.3.1.6.5    | Nomenclature                                               | 411 |
| 7.3.1.6.6    | Wheelset steering concepts                                 | 413 |
| 7.3.1.7      | Main components of a bogie                                 | 415 |
| 7.3.1.7.1    | Wheelset                                                   | 415 |
| 7.3.1.7.2    | Single wheels                                              | 418 |
| 7.3.1.7.3    | Axle bearings                                              | 419 |
| 7.3.1.7.4    | Bogie frame                                                | 420 |
| 7.3.1.7.4.1  | Overview                                                   | 420 |
| 7.3.1.7.4.2  | Architecture                                               | 421 |
| 7.3.1.7.4.3  | Dimensioning                                               | 421 |
| 7.3.1.7.4.4  | Materials                                                  | 422 |
| 7.3.1.7.4.5  | Standards                                                  | 423 |
| 7.3.1.7.4.6  | Validation plan for bogie frames                           | 423 |
| 7.3.1.7.4.7  | The static test phase                                      | 423 |
| 7.3.1.7.4.8  | The dynamic test phase                                     | 425 |
| 7.3.1.7.4.9  | Tests on railway tracks                                    | 426 |
| 7.3.1.7.5    | Axle guidance and primary suspension                       | 426 |
| 7.3.1.7.6    | Secondary suspension and interfaces to the carbody         | 427 |
| 7.3.1.7.7    | Integration of traction                                    | 431 |
| 7.3.1.7.8    | Integration of brakes                                      | 434 |
| 7.3.1.7.9    | Add-on functions                                           | 435 |
| 7.3.1.7.10   | Mechatronic elements within a bogie                        | 437 |
| 7.3.1.7.11   | Suspension components                                      | 438 |
| 7.3.1.8      | Some examples of running gear                              | 442 |
| 7.3.1.8.1    | Tram running gear                                          | 442 |
| 7.3.1.8.2    | A bogie of a four-axle passenger coach                     | 442 |
| 7.3.1.8.3    | High-speed train bogies                                    | 443 |
| 7.3.1.8.4    | The single axle running gear of the Copenhagen S-Tog       | 444 |
| 7.3.1.8.5    | Running gear of a two-axle freight wagon                   | 445 |
| 7.3.1.8.6    | Bogies of a four-axle freight wagon                        | 445 |
| 7.3.1.8.7    | A locomotive bogie                                         | 446 |
| 7.3.1.9      | The mechatronic bogie                                      | 446 |
| 7.3.1.9.1    | Introduction                                               | 446 |
| 7.3.1.9.2    | Overview                                                   | 447 |
| 7.3.1.9.3    | Wheelset guiding: Active Radial Steering (ARS)             | 447 |
| 7.3.1.9.4    | Secondary Active Lateral Suspension (ALS)                  | 448 |
| 7.3.1.9.5    | Secondary Active Vertical Suspension (AVS)                 | 448 |
| 7.3.1.9.6    | Bogie to carbody roll (WAKO)                               | 449 |
| 7.3.1.9.7    | Condition monitoring                                       | 450 |
| 7.3.1.10     | Rubber-tyred running gear                                  | 451 |
| 7.3.1.10.1   | General principle                                          | 451 |
| 7.3.1.10.2   | The carbody load carrying system                           | 451 |
| 7.3.1.10.3   | Guidance principle over the permanent way                  | 452 |
| 7.3.1.10.3.1 | Running gear classification for tyre-mounted metro systems | 452 |
| 7.3.1.10.3.2 | The most widespread design                                 | 454 |
| 7.3.1.10.3.3 | The VAL System                                             | 456 |
| 7.3.1.10.3.4 | The NEOVAL System                                          | 457 |
| 7.3.1.10.3.5 | The other systems                                          | 458 |

|                      |                                                              |     |
|----------------------|--------------------------------------------------------------|-----|
| 7.3.1.10.4           | The carrying tyre                                            | 458 |
| 7.3.1.10.4.1         | General                                                      | 458 |
| 7.3.1.10.4.2         | Adhesion                                                     | 459 |
| 7.3.1.10.4.3         | Rolling resistance                                           | 460 |
| 7.3.1.10.4.4         | Managing fire hazards                                        | 460 |
| 7.3.1.10.5           | The guide tyre                                               | 461 |
| 7.3.1.10.6           | The kinematic transmission drive                             | 461 |
| 7.3.1.10.6.1         | The most widespread transmission system                      | 461 |
| 7.3.1.10.6.2         | Movement transmission for the NEOVAL axle                    | 463 |
| 7.3.1.10.7           | Traction                                                     | 464 |
| 7.3.1.10.8           | Current collection                                           | 464 |
| 7.3.2                | Tilting                                                      | 466 |
| 7.3.2.1              | Motivation                                                   | 466 |
| 7.3.2.2              | Principles and definitions                                   | 466 |
| 7.3.2.3              | Performances                                                 | 467 |
| 7.3.2.3.1            | Performance improvement                                      | 467 |
| 7.3.2.3.2            | Limitations                                                  | 469 |
| 7.3.2.4              | Technical implementations                                    | 469 |
| 7.3.2.4.1            | System aspects                                               | 469 |
| 7.3.2.4.2            | Kinematic mechanisms                                         | 470 |
| 7.3.2.4.2.1          | General                                                      | 470 |
| 7.3.2.4.2.2          | Impact on vehicle cross-section                              | 470 |
| 7.3.2.4.2.3          | Impact on passive centring capability                        | 470 |
| 7.3.2.4.2.4          | Impact on change of vertical load on the wheels              | 470 |
| 7.3.2.4.2.5          | Impact on the position of the pantograph versus the catenary | 471 |
| 7.3.2.4.3            | Passive carbody tilting mechanism                            | 471 |
| 7.3.2.4.4            | Active carbody tilting mechanism                             | 471 |
| 7.3.2.4.4.1          | Carbody tilting mechanism design                             | 472 |
| 7.3.2.4.4.2          | Pantograph counter-tilting mechanism                         | 473 |
| 7.3.2.4.5            | Control                                                      | 474 |
| 7.3.2.4.5.1          | Reactive tilt control                                        | 474 |
| 7.3.2.4.5.2          | Anticipative control                                         | 475 |
| 7.3.2.4.5.3          | Tilt Compensation Factor                                     | 476 |
| 7.3.2.4.5.4          | Pantograph tilt control                                      | 477 |
| 7.3.2.4.6            | Tilt actuation                                               | 477 |
| 7.3.2.4.6.1          | General                                                      | 477 |
| 7.3.2.4.6.2          | Actuation types                                              | 477 |
| 7.3.2.4.6.3          | Actuation specifics                                          | 479 |
| 7.3.2.4.6.4          | Damping                                                      | 480 |
| 7.3.2.5              | Comfort                                                      | 480 |
| 7.3.2.5.1            | General                                                      | 480 |
| 7.3.2.5.2            | Discomfort                                                   | 480 |
| 7.3.2.5.3            | Assessment criteria                                          | 481 |
| 7.3.2.5.3.1          | Passenger comfort in transitions - PCT (EN 12299)            | 481 |
| 7.3.2.5.3.2          | Passenger comfort on discrete events - PDE (EN 12299)        | 482 |
| 7.3.2.6              | Operational aspects                                          | 482 |
| 7.3.2.7              | Economic aspects                                             | 483 |
| 7.3.3                | Automatic gauge change-over systems                          | 485 |
| 7.3.3.1              | Context and needs                                            | 485 |
| 7.3.3.2              | Technical and safety challenges                              | 486 |
| 7.3.3.3              | Brief technical description and available solutions          | 486 |
| 7.3.3.4              | Outlook                                                      | 491 |
| 7.3.3.4.1            | Compatibility between systems                                | 491 |
| 7.3.3.4.2            | Extended use for freight trains                              | 491 |
| 7.3.3.4.3            | Technical standardisation                                    | 491 |
| 7.4                  | Assessment of the running dynamics of vehicles               | 492 |
| 1 <sup>st</sup> step | - Preliminary approval tests:                                | 492 |
| 2 <sup>nd</sup> step | - 'On-track' tests:                                          | 492 |
| 7.4.1                | Safety against derailment on twisted track                   | 492 |
| 7.4.2                | Running dynamic behaviour (On-track testing)                 | 493 |



|           |                                                            |     |
|-----------|------------------------------------------------------------|-----|
| 7.5       | Buffing and draw gear components                           | 498 |
| 7.5.1     | Definition and missions                                    | 498 |
| 7.5.2     | The end couplers                                           | 499 |
| 7.5.2.1   | Scope                                                      | 499 |
| 7.5.2.2   | The manual couplers                                        | 499 |
| 7.5.2.2.1 | The manual UIC coupler                                     | 499 |
| 7.5.2.2.2 | Other manual couplers                                      | 501 |
| 7.5.2.3   | Semi-automatic couplers                                    | 501 |
| 7.5.2.3.1 | The Janney or AAR coupler                                  | 501 |
| 7.5.2.3.2 | The Willison coupler and the Russian SA-3 coupler          | 502 |
| 7.5.2.3.3 | The European automatic coupler                             | 503 |
| 7.5.2.4   | The automatic couplers                                     | 504 |
| 7.5.2.4.1 | The Scharfenberg coupler                                   | 504 |
| 7.5.2.4.2 | Other automatic couplers                                   | 505 |
| 7.5.3     | The internal couplers                                      | 505 |
| 7.5.4     | Protection against overriding                              | 508 |
|           | The authors                                                | 510 |
|           | Acknowledgments                                            | 514 |
|           | Abbreviations                                              | 515 |
|           | Bibliography                                               | 520 |
|           | Rolling Stock in the Railway System – Overview of contents | 532 |



*Freight and passenger trains crossing at Muttensz station in Switzerland (Reinhard Christeller)*

